



Model	A11	
Part Number	HX-01003	
Material	316/316L	
Overall Dimensions (Core) (W x L x H)	1 x 10 x 0.98 in	25.4 x 254 x 25 mm
Length (between side nozzle centers)	8.9 in	226 mm
Max Pressure	2616 psig (@302°F)	180.4 barg (@150°C)
Max Temperature	1000°F (@2000 psig)	538°C (@137.9 barg)
Surface Area (Side A)	0.667 ft ²	0.0619 m ²
Surface Area (Side B)	0.777 ft ²	0.0722 m ²
Internal Volume (Side A)	0.0052 gal	0.0195 lt
Internal Volume (Side B)	0.0062 gal	0.0236 lt
Connector (in)	NPT 3/8 Female	

Model	A11	
Part Number	HX-01005	
Material	Al 6061	
Overall Dimensions (Core) (W x L x H)	1 x 10 x 0.98 in	25.4 x 254 x 25 mm
Length (between side nozzle centers)	8.9 in	226 mm
Max Pressure	1800 psig (@224.8°F)	124.1 barg (@107.1°C)
Max Temperature	392°F (@715.7 psig)	200°C (@49.3 barg)
Surface Area (Side A)	0.667 ft ²	0.0619 m ²
Surface Area (Side B)	0.777 ft ²	0.0722 m ²
Internal Volume (Side A)	0.0052 gal	0.0195 lt
Internal Volume (Side B)	0.0062 gal	0.0236 lt
Connector (in)	NPT 3/8 Female	



Model	A11	
Part Number	HX-01006	
Material	Ti Grade 2	
Overall Dimensions (Core) (W x L x H)	1 x 10 x 0.98 in	25.4 x 254 x 25 mm
Length (between side nozzle centers)	8.9 in	226 mm
Max Pressure	1800 psig (@307°F)	124.1 barg (@153°C)
Max Temperature	617°F (@1123 psig)	325°C (@77.4 barg)
Surface Area (Side A)	0.667 ft ²	0.0619 m ²
Surface Area (Side B)	0.777 ft ²	0.0722 m ²
Internal Volume (Side A)	0.0052 gal	0.0195 lt
Internal Volume (Side B)	0.0062 gal	0.0236 lt
Connector (in)	NPT 3/8 Female	