



Model	A21	
Part Number	HX-01028	
Material	316/316L	
Overall Dimensions (Core) (W x L x H)	1.5 x 10 x 1.51 in	38.1 x 254 x 38.25 mm
Length (between side nozzle centers)	8.52 in	216.5 mm
Max Pressure	2616 psig (@302°F)	180.4 barg (@150°C)
Max Temperature	1000°F (@2000 psig)	538°C (@137.9 barg)
Surface Area (Side A)	1.895 ft ²	0.1760 m ²
Surface Area (Side B)	1.877 ft ²	0.1744 m ²
Internal Volume (Side A)	0.0147 gal	0.0558 lt
Internal Volume (Side B)	0.0156 gal	0.059 lt
Connector (in)	NPT 1/2 Female	

Model	A21	
Part Number	HX-01035	
Material	Al 6061	
Overall Dimensions (Core) (W x L x H)	1.5 x 10 x 1.51 in	38.1 x 254 x 38.25 mm
Length (between side nozzle centers)	8.52 in	216.5 mm
Max Pressure	1800 psig (@224.8°F)	124.1 barg (@107.1°C)
Max Temperature	392°F (@715.7 psig)	200°C (@49.3 barg)
Surface Area (Side A)	1.895 ft ²	0.1760 m ²
Surface Area (Side B)	1.877 ft ²	0.1744 m ²
Internal Volume (Side A)	0.0147 gal	0.0558 lt
Internal Volume (Side B)	0.0156 gal	0.059 lt
Connector (in)	NPT 1/2 Female	



Model	A21	
Part Number	HX-01036	
Material	Ti Grade 2	
Overall Dimensions (Core) (W x L x H)	1.5 x 10 x 1.51 in	38.1 x 254 x 38.25 mm
Length (between side nozzle centers)	8.52 in	216.5 mm
Max Pressure	1800 psig (@307°F)	124.1 barg (@153°C)
Max Temperature	617°F (@1123 psig)	325°C (@77.4 barg)
Surface Area (Side A)	1.895 ft ²	0.1760 m ²
Surface Area (Side B)	1.877 ft ²	0.1744 m ²
Internal Volume (Side A)	0.0147 gal	0.0558 lt
Internal Volume (Side B)	0.0156 gal	0.059 lt
Connector (in)	NPT 1/2 Female	