



Model	A32	
Part Number	HX-01031	
Material	316/316L	
Overall Dimensions (Core) (W x L x H)	2 x 20 x 2.03 in	50.8 x 508 x 51.5 mm
Length (between side nozzle centers)	2616 psig (@302°F)	180.4 barg (@150°C)
Max Pressure	1000°F (@2000 psig)	538°C (@137.9 barg)
Max Temperature	1018°F	548°C
Surface Area (Side A)	6.886 ft ²	0.6397 m ²
Surface Area (Side B)	7.357 ft ²	0.6834 m ²
Internal Volume (Side A)	0.0511 gal	0.1935 lt
Internal Volume (Side B)	0.0574 gal	0.2173 lt
Connector (in)	3/4 NPT Female	

Model	A32	
Part Number	HX-01043	
Material	Al 6061	
Overall Dimensions (Core) (W x L x H)	2 x 20 x 2.03 in	50.8 x 508 x 51.5 mm
Length (between side nozzle centers)	18.03 in	458 mm
Max Pressure	1800 psig (@224.8°F)	124.1 barg (@107.1°C)
Max Temperature	392°F (@715.7 psig)	200°C (@49.3 barg)
Surface Area (Side A)	6.886 ft ²	0.6397 m ²
Surface Area (Side B)	7.357 ft ²	0.6834 m ²
Internal Volume (Side A)	0.0511 gal	0.1935 lt
Internal Volume (Side B)	0.0574 gal	0.2173 lt
Connector (in)	3/4 NPT Female	



Model	A32	
Part Number	HX-01044	
Material	Ti Grade 2	
Overall Dimensions (Core) (W x L x H)	2 x 20 x 2.03 in	50.8 x 508 x 51.5 mm
Length (between side nozzle centers)	18.03 in	458 mm
Max Pressure	1800 psig (@307°F)	124.1 barg (@153°C)
Max Temperature	617°F (@1123 psig)	325°C (@77.4 barg)
Surface Area (Side A)	6.886 ft ²	0.6397 m ²
Surface Area (Side B)	7.357 ft ²	0.6834 m ²
Internal Volume (Side A)	0.0511 gal	0.1935 lt
Internal Volume (Side B)	0.0574 gal	0.2173 lt
Connector (in)	3/4 NPT Female	