



Model	A43	
Part Number	HX-01056	
Material	316/316L	
Overall Dimensions (Core) (W x L x H)	2.5 x 30 x 2.5 in	63.5 x 762 x 63.4 mm
Length (between side nozzle centers)	27.64 in	702 mm
Max Pressure	2616 psig (@302°F)	180.4 barg (@150°C)
Max Temperature	1000°F (@2000 psig)	538°C (@137.9 barg)
Surface Area (Side A)	16.514 ft ²	1.5342 m ²
Surface Area (Side B)	17.357 ft ²	1.6126 m ²
Internal Volume (Side A)	0.1192 gal	0.4513 Lt
Internal Volume (Side B)	0.1315 gal	0.4977 Lt
Connector (in)	1 NPT Female	

Model	A43	
Part Number	HX-01057	
Material	Al 6061	
Overall Dimensions (Core) (W x L x H)	2.5 x 30 x 2.5 in	63.5 x 762 x 63.4 mm
Length (between side nozzle centers)	27.64 in	702 mm
Max Pressure	1800 psig (@224.8°F)	124.1 barg (@107.1°C)
Max Temperature	392°F (@715.7 psig)	200°C (@49.3 barg)
Surface Area (Side A)	16.514 ft ²	1.5342 m ²
Surface Area (Side B)	17.357 ft ²	1.6126 m ²
Internal Volume (Side A)	0.1192 gal	0.4513 Lt
Internal Volume (Side B)	0.1315 gal	0.4977 Lt
Connector (in)	1 NPT Female	



Model	A43	
Part Number	HX-01058	
Material	Ti Grade 2	
Overall Dimensions (Core) (W x L x H)	2.5 x 30 x 2.5 in	63.5 x 762 x 63.4 mm
Length (between side nozzle centers)	27.64 in	702 mm
Max Pressure	1800 psig (@307°F)	124.1 barg (@153°C)
Max Temperature	617°F (@1123 psig)	325°C (@77.4 barg)
Surface Area (Side A)	16.514 ft ²	1.5342 m ²
Surface Area (Side B)	17.357 ft ²	1.6126 m ²
Internal Volume (Side A)	0.1192 gal	0.4513 Lt
Internal Volume (Side B)	0.1315 gal	0.4977 Lt
Connector (in)	1 NPT Female	