

Model	B11	
Part Number	HX-01013	
Material	316/316L	
Overall Dimensions (Core) (W x L x H)	3 x 10 x 1.56 in	76.2 x 254 x 39.5 mm
Length (between side nozzle centers)	8.16 in	207.4 mm
Max Pressure	2616 psig (@302°F)	180.4 barg (@150°C)
Max Temperature	1000°F (@2000 psig)	538°C (@137.9 barg)
Surface Area (Side A)	2.501 ft ²	0.2324 m ²
Surface Area (Side B)	2.772 ft ²	0.2575 m ²
Internal Volume (Side A)	0.0225 gal	0.0853 lt
Internal Volume (Side B)	0.0246 gal	0.0930 lt
Connector (in)	3/4 NPT Male	

Model	B11	
Part Number	HX-01024	
Material	Al 6061	
Overall Dimensions (Core) (W x L x H)	3 x 10 x 1.56 in	76.2 x 254 x 39.5 mm
Length (between side nozzle centers)	8.16 in	207.4 mm
Max Pressure	1800 psig (@224.8°F)	124.1 barg (@107.1°C)
Max Temperature	392°F (@715.7 psig)	200°C (@49.3 barg)
Surface Area (Side A)	2.501 ft ²	0.2324 m ²
Surface Area (Side B)	2.772 ft ²	0.2575 m ²
Internal Volume (Side A)	0.0225 gal	0.0853 lt
Internal Volume (Side B)	0.0246 gal	0.0930 lt
Connector (in)	3/4 NPT Male	



Model	B11	
Part Number	HX-01023	
Material	Ti Grade 2	
Overall Dimensions (Core) (W x L x H)	3 x 10 x 1.56 in	76.2 x 254 x 39.5 mm
Length (between side nozzle centers)	8.16 in	207.4 mm
Max Pressure	1800 psig (@307°F)	124.1 barg (@153°C)
Max Temperature	617°F (@1123 psig)	325°C (@77.4 barg)
Surface Area (Side A)	2.501 ft ²	0.2324 m ²
Surface Area (Side B)	2.772 ft ²	0.2575 m ²
Internal Volume (Side A)	0.0225 gal	0.0853 lt
Internal Volume (Side B)	0.0246 gal	0.0930 lt
Connector (in)	3/4 NPT Male	