



Model	B12	
Part Number	HX-01021	
Material	316/316L	
Overall Dimensions (Core) (W x L x H)	3 x 16 x 1.56 in	76.2 x 406.4 x 39.5 mm
Length (between side nozzle centers)	14.16 in	359.8 mm
Max Pressure	2616 psig (@302°F)	180.4 barg (@150°C)
Max Temperature	1000°F (@2000 psig)	538°C (@137.9 barg)
Surface Area (Side A)	4.710 ft ²	0.4376 m ²
Surface Area (Side B)	5.207 ft ²	0.4838 m ²
Internal Volume (Side A)	0.0364 gal	0.1379 lt
Internal Volume (Side B)	0.0401 gal	0.1516 lt
Connector (in)	3/4 NPT Male	

Model	B12	
Part Number	HX-01065	
Material	Al 6061	
Overall Dimensions (Core) (W x L x H)	3 x 16 x 1.56 in	76.2 x 406.4 x 39.5 mm
Length (between side nozzle centers)	14.16 in	359.8 mm
Max Pressure	1800 psig (@224.8°F)	124.1 barg (@107.1°C)
Max Temperature	392°F (@715.7 psig)	200°C (@49.3 barg)
Surface Area (Side A)	4.710 ft ²	0.4376 m ²
Surface Area (Side B)	5.207 ft ²	0.4838 m ²
Internal Volume (Side A)	0.0364 gal	0.1379 lt
Internal Volume (Side B)	0.0401 gal	0.1516 lt
Connector (in)	3/4 NPT Male	



Model	B12	
Part Number	HX-01025	
Material	Ti Grade 2	
Overall Dimensions (Core) (W x L x H)	3 x 16 x 1.56 in	76.2 x 406.4 x 39.5 mm
Length (between side nozzle centers)	14.16 in	359.8 mm
Max Pressure	1800 psig (@307°F)	124.1 barg (@153°C)
Max Temperature	617°F (@1123 psig)	325°C (@77.4 barg)
Surface Area (Side A)	4.710 ft ²	0.4376 m ²
Surface Area (Side B)	5.207 ft ²	0.4838 m ²
Internal Volume (Side A)	0.0364 gal	0.1379 lt
Internal Volume (Side B)	0.0401 gal	0.1516 lt
Connector (in)	3/4 NPT Male	