



Model	B22	
Part Number	HX-01066	
Material	316/316L	
Overall Dimensions (Core) (W x L x H)	3 x 16 x 2.03 in	76.2 x 406.4 x 51.5 mm
Length (between side nozzle centers)	14.16 in	359.8 mm
Max Pressure	2616 psig (@302°F)	180.4 barg (@150°C)
Max Temperature	1000°F (@2000 psig)	538°C (@137.9 barg)
Surface Area (Side A)	6.804 ft <sup>2</sup>	0.6321 m <sup>2</sup>
Surface Area (Side B)	7.290 ft <sup>2</sup>	0.6773 m <sup>2</sup>
Internal Volume (Side A)	0.0526 gal	0.1989 lt
Internal Volume (Side B)	0.0563 gal	0.2131 lt
Connector (in)	3/4 NPT Male	

Model	B22	
Part Number	HX-01067	
Material	Al 6061	
Overall Dimensions (Core) (W x L x H)	3 x 16 x 2.03 in	76.2 x 406.4 x 51.5 mm
Length (between side nozzle centers)	14.16 in	359.8 mm
Max Pressure	1800 psig (@224.8°F)	124.1 barg (@107.1°C)
Max Temperature	392°F (@715.7 psig)	200°C (@49.3 barg)
Surface Area (Side A)	6.804 ft <sup>2</sup>	0.6321 m <sup>2</sup>
Surface Area (Side B)	7.290 ft <sup>2</sup>	0.6773 m <sup>2</sup>
Internal Volume (Side A)	0.0526 gal	0.1989 lt
Internal Volume (Side B)	0.0563 gal	0.2131 lt
Connector (in)	3/4 NPT Male	



<b>Model</b>	<b>B22</b>	
<b>Part Number</b>	HX-01068	
<b>Material</b>	Ti Grade 2	
<b>Overall Dimensions (Core) (W x L x H)</b>	3 x 16 x 2.03 in	76.2 x 406.4 x 51.5 mm
<b>Length (between side nozzle centers)</b>	14.16 in	359.8 mm
<b>Max Pressure</b>	1800 psig (@307°F)	124.1 barg (@153°C)
<b>Max Temperature</b>	617°F (@1123 psig)	325°C (@77.4 barg)
<b>Surface Area (Side A)</b>	6.804 ft <sup>2</sup>	0.6321 m <sup>2</sup>
<b>Surface Area (Side B)</b>	7.290 ft <sup>2</sup>	0.6773 m <sup>2</sup>
<b>Internal Volume (Side A)</b>	0.0526 gal	0.1989 lt
<b>Internal Volume (Side B)</b>	0.0563 gal	0.2131 lt
<b>Connector (in)</b>	3/4 NPT Male	