



Model	B23	
Part Number	HX-01073	
Material	316/316L	
Overall Dimensions (Core) (W x L x H)	4 x 12 x 2.03 in	101.6 x 304.8 x 51.5 mm
Length (between side nozzle centers)	9.89 in	251.2 mm
Max Pressure	2616 psig (@302°F)	180.4 barg (@150°C)
Max Temperature	1000°F (@2000 psig)	538°C (@137.9 barg)
Surface Area (Side A)	6.226 ft <sup>2</sup>	0.5784 m <sup>2</sup>
Surface Area (Side B)	6.758 ft <sup>2</sup>	0.6278 m <sup>2</sup>
Internal Volume (Side A)	0.0533 gal	0.2017 lt
Internal Volume (Side B)	0.0569 gal	0.2154 lt
Connector (in)	1 NPT Male	

Model	B23	
Part Number	HX-01074	
Material	Al 6061	
Overall Dimensions (Core) (W x L x H)	4 x 12 x 2.03 in	101.6 x 304.8 x 51.5 mm
Length (between side nozzle centers)	9.89 in	251.2 mm
Max Pressure	1800 psig (@224.8°F)	124.1 barg (@107.1°C)
Max Temperature	392°F (@715.7 psig)	200°C (@49.3 barg)
Surface Area (Side A)	6.226 ft <sup>2</sup>	0.5784 m <sup>2</sup>
Surface Area (Side B)	6.758 ft <sup>2</sup>	0.6278 m <sup>2</sup>
Internal Volume (Side A)	0.0533 gal	0.2017 lt
Internal Volume (Side B)	0.0569 gal	0.2154 lt
Connector (in)	1 NPT Male	



<b>Model</b>	<b>B23</b>	
<b>Part Number</b>	HX-01075	
<b>Material</b>	Ti Grade 2	
<b>Overall Dimensions (Core) (W x L x H)</b>	4 x 12 x 2.03 in	101.6 x 304.8 x 51.5 mm
<b>Length (between side nozzle centers)</b>	9.89 in	251.2 mm
<b>Max Pressure</b>	1800 psig (@307°F)	124.1 barg (@153°C)
<b>Max Temperature</b>	617°F (@1123 psig)	325°C (@77.4 barg)
<b>Surface Area (Side A)</b>	6.226 ft <sup>2</sup>	0.5784 m <sup>2</sup>
<b>Surface Area (Side B)</b>	6.758 ft <sup>2</sup>	0.6278 m <sup>2</sup>
<b>Internal Volume (Side A)</b>	0.0533 gal	0.2017 lt
<b>Internal Volume (Side B)</b>	0.0569 gal	0.2154 lt
<b>Connector (in)</b>	1 NPT Male	