



Model	B24	
Part Number	HX-01081	
Material	316/316L	
Overall Dimensions (Core) (W x L x H)	4 x 24 x 2.03 in	101.6 x 609.6 x 51.5 mm
Length (between side nozzle centers)	21.89 in	556.0 mm
Max Pressure	2616 psig (@302°F)	180.4 barg (@150°C)
Max Temperature	1000°F (@2000 psig)	538°C (@137.9 barg)
Surface Area (Side A)	14.847 ft ²	1.3793 m ²
Surface Area (Side B)	16.065 ft ²	1.4925 m ²
Internal Volume (Side A)	0.1090 gal	0.4126 lt
Internal Volume (Side B)	0.1170 gal	0.4428 lt
Connector (in)	1 NPT Male	

Model	B24	
Part Number	HX-01082	
Material	Al 6061	
Overall Dimensions (Core) (W x L x H)	4 x 24 x 2.03 in	101.6 x 609.6 x 51.5 mm
Length (between side nozzle centers)	21.89 in	556.0 mm
Max Pressure	1800 psig (@224.8°F)	124.1 barg (@107.1°C)
Max Temperature	392°F (@715.7 psig)	200°C (@49.3 barg)
Surface Area (Side A)	14.847 ft ²	1.3793 m ²
Surface Area (Side B)	16.065 ft ²	1.4925 m ²
Internal Volume (Side A)	0.1090 gal	0.4126 lt
Internal Volume (Side B)	0.1170 gal	0.4428 lt
Connector (in)	1 NPT Male	



Model	B24	
Part Number	HX-01083	
Material	Ti Grade 2	
Overall Dimensions (Core) (W x L x H)	4 x 24 x 2.03 in	101.6 x 609.6 x 51.5 mm
Length (between side nozzle centers)	21.89 in	556.0 mm
Max Pressure	1800 psig (@307°F)	124.1 barg (@153°C)
Max Temperature	617°F (@1123 psig)	325°C (@77.4 barg)
Surface Area (Side A)	14.847 ft ²	1.3793 m ²
Surface Area (Side B)	16.065 ft ²	1.4925 m ²
Internal Volume (Side A)	0.1090 gal	0.4126 lt
Internal Volume (Side B)	0.1170 gal	0.4428 lt
Connector (in)	1 NPT Male	